



# Material Safety Data Sheet

## SECTION I – MANUFACTURERS INFORMATION

PRODUCT NAME: 84XX Epoxy Primer  
MSDS PREPARATION DATE: 4-1-2015  
MANUFACTURER FOR: NEXERA PRO FINISHES  
HOUSTON, TX  
PRODUCT INFORMATION: (888) 411-8951  
EMERGENCY TELEPHONE: CHEMTREC: 800-424-9300

While we believe that the data herein is accurate & derived from quality sources, this data is not to be taken as a warrantee or product liability. It is offered solely for your consideration and personal protection.

## SECTION II – HAZARDOUS INGREDIENTS

Ingredients	CAS Number	Vapor Pressure (mm HG @temp)	Weight Percent
*XYLENE	1330-20-7	9.5 mm Hg @68°F	18 – 22%
*METHYL ISOBUTYL KETONE	108-10-1	16 mm Hg @68°F	5 - 10 %
*N BUTYL ACETATE	123-86-4	7.8 mm Hg @68°F	0 - 5%
ISOPROPYL ALCOHOL 99%	67-63-0	31.2 mm Hg @68°F	0 - 5%

\* Indicates toxic chemicals subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

## SECTION III – PHYSICAL DATA

Boiling Point: 241°F	Vapor Pressure (mm Hg): @ 77°F= 23.0
Vapor Density (Air=1): Heavier than air	Melting Point (°C): N/A
Specific Gravity. 1.25 – 1.4	Solubility in Water: none
Evaporation Rate: Slower than Ether	Appearance and Odor: Clear – Mild
V.O.C. 3.4 - 4.2 lbs/gal.	Weight Solids: 61-66 %

## SECTION IV – FIRE AND EXPLOSION DATA

Flash Point (Method Used): T.C.C., 60 - 90°F  
Flammable Explosion: LEL = 1.0% UEL = 12.3%  
Extinguishing Media: (1) Dry Chemical, (2) CO2, (3) Foam

Special Fire Fighting Procedures: Dry Chemical, Carbon Dioxide, Water Spray or Regular Foam. Full protective equipment including self-contained breathing apparatus should be used. If water is used, fog nozzles are preferable. Water may be used to cool dosed containers to prevent pressure buildup due to extreme heat. CAUTION: A straight stream of water will spread fire.

Unusual Fire and Explosion Hazards: Vapor accumulation will flash and/or explode, if ignited. Containers may burst explosively if overheated in fire. Cool with water spray or fog. Empty containers also present fire explosion hazard due to residual vapors. Keep containers tightly dosed. During emergency situations, over-exposure to decomposition products may cause a health hazard with no symptoms immediately apparent. Obtain medical attention.

## **SECTION V – HEALTH HAZARD DATA**

### **EFFECTS OF OVEREXPOSURE:**

**ACUTE:** Inhalation: Anesthetic. Irritation of respiratory tract or acute nervous system depression. Overexposure may result in headaches and nausea possibly followed by loss of consciousness. Ingestion: Gastrointestinal irritation including vomiting can occur. Aspiration of material into lungs may result in chemical pneumonitis which can be fatal. Skin contact: may result in irritation and absorption through skin. Eye contact will irritate.

**CHRONIC:** Some reports have associated repeated, prolonged overexposure to solvents with permanent central nervous system changes. Misuse by concentrating and inhaling the contents may be harmful or fatal. See Target Organ Effects Sheet for further information about effects of overexposure and medical conditions generally aggravated by exposure. The Target Organ Effects Sheet is an integral part of this Material Safety Data Sheet: any duplication of the MSDS must include it. California Proposition 65 requires that warnings be given regarding exposures to chemicals listed by the State as being known to cause cancer, birth defects or other reproductive harm. This product is not intentionally formulated with chemicals that are listed by California as causing the above effects. However, we are informed by the suppliers of some chemical ingredients used in this product that they may contain trace, but detectable, levels of some listed chemicals as impurities. Therefore, trace, but detectable, levels of listed chemicals may be present in this product.

### **EMERGENCY & FIRST AID PROCEDURES:**

Vapor Inhalation – Restore breathing. Remove to fresh air. Keep warm and quiet. Notify a physician.

Eye Contact – Flush IMMEDIATELY with copious amounts of running water for at least 15 minutes.

Take to physician for definitive medical treatment.

Skin Contact – Clean and wash affected area with water. Consult a physician if needed.

Ingestion – Drink 1 or 2 glasses of water to dilute. DO NOT INDUCE VOMITING! Call physician immediately

## **SECTION VI – REACTIVITY DATA**

**STABILITY:** Stable

**CONDITIONS TO AVOID:** Heat, open flames, electrical and static discharge.

**INCOMPATIBILITY:** (materials to avoid): Strong oxidizers.

**HAZARDOUS DECOMPOSITION PRODUCTS:** May produce hazardous fumes when heated to decomposition as in welding.

**HAZARDOUS POLYMERIZATION:** Will not occur.

## **SECTION VII – SPILL OR LEAK PROCEDURES**

**STEPS IF SPILLED:** Ventilate area. Remove all possible sources of ignition. Avoid prolonged breathing of vapors. Confine spill with Inert absorbent and clean up with spark-proof tools.

**WASTE DISPOSAL:** Dispose of in accordance with local, state, and federal regulations. Landfill or incinerate only in approved facility by licensed contractor. Do not incinerate in closed container.

## **SECTION VIII – SPECIAL PROTECTION INFORMATION**

**RESPIRATORY PROTECTION:** Use NIOSH/MSHA TC23C Chemical / Mechanical type filter system to remove a combination of particles, gas & vapors. Use an air supplied respirator if necessary.

**VENTILATION:** Use adequate ventilation in volume and pattern to keep TLV's and PEL's below recommended limits. General mechanical ventilation should comply with OSHA 1910.94.

**PROTECTIVE GLOVES:** To prevent prolonged exposure, use rubber gloves. Solvents may be absorbed through the skin.

**EYE PROTECTION:** Safety glasses or goggles with splashguards of side shields.

**OTHER PROTECTIVE EQUIPMENT:** Prevent prolonged skin contact to contaminated clothing.

## **SECTION IX – SPECIAL PRECAUTIONS**

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:** Observe label precautions. Keep away from heat, sparks and flame. Close container after each use. Ground containers when pouring. Wash all exposed areas thoroughly after handling and before eating or smoking. Do not store above 120°F.

**OTHER PRECAUTIONS:** Do not sand, flame cut, braze or weld dry coating without a NIOSH/MSHA approved respirator or appropriate ventilation.

**‘FOR INDUSTRIAL USE ONLY’**

**DO NOT TAKE INTERNALLY. IF INGESTED, DO NOT INDUCE VOMITING. CONSULT A PHYSICIAN. DO NOT FLAME CUT, WELD, OR BRAZE ON COATED MATERIAL WITHOUT NIOSA/MSHA TC23C RESPIRATOR.**

**DISCLAIMER:**

**WARNING: KEEP THIS AND ALL PAINT RELATED PRODUCTS OUT OF THE REACH OF CHILDREN!**

The information contained in this MSDS is based on data from sources considered to be reliable but we do not guarantee the accuracy or completeness thereof. We urge each customer or recipient of this MSDS to study it carefully to become aware of and understand the hazards associated with this product. The reader should consider consulting reference works or individuals who are experts in ventilation, toxicology or fire prevention as necessary or appropriate to use and understand the data in this MSDS.

Note: The data on this MSDS relates only to individual components and does not represent the end mixed product.

Health: - 2

Flammability: - 3

Reactivity: - 0

## **SECTION X – TRANSPORTATION INFORMATION**

<b>DOT SHIPPING NAME:</b>	PAINT
<b>HAZARD CLASS:</b>	3
<b>UN NUMBER:</b>	UN1263
<b>PACKING GROUP:</b>	II (2)
<b>EMERGENCY RESPONSE GUIDE #:</b>	128