

**PRODUCT: NEX6010 CUSTOM FILLING SYSTEM****Section 01: Chemical product and company identification**

Product name..... NEX6010 CUSTOM FILLING SYSTEM
 Manufactured for..... AUTO REFINISH DISTRIBUTORS INC
 PO Box 38484
 Houston, TX 77238

24 hour emergency number..... IN CANADA CALL CANUTEC (613) 996-6666-IN THE UNITED STATES CALL
 CHEMTREC (800) 424-9300.

Material use..... Paint reducer.
 Chemical family..... Mixture.
 Preparation date..... October 4, 2013.
 Hazard rate
 NFPA rating..... Health: 2 Fire: 4 Reactivity: 0.
 HMIS..... H: 2 F: 4 R: 0.

Section 02: Hazards identification

Signal Word..... DANGER.
 Hazard Classification..... Aspiration Toxicity 2. Flammable Aerosol 2. Acute Toxicity 3. STOT SE 3. Skin Sensitizer 1B.
 Hazard Description..... H302 Harmful if swallowed. H223 Flammable aerosol . H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.
 Precautionary Statements..... P243 Take precautionary measures against static discharge. P251 Do not pierce or burn container, even after use. P261 Avoid breathing mists, vapours and sprays. P264 Wash thoroughly after handling. P270 Do not eat drink or smoke while using this product. P271 Use only outdoors or in a well ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves and eye protection. P202 Do not handle this product until all safety instructions have been read and understood. P284 In case of inadequate ventilation wear respiratory protection. P410 Protect from sunlight. P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P211 Do not spray on an open flame or other ignition sources. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion proof equipment. P242 Use only non-sparking tools.

Section 03: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredients	CAS #	Wt. %
ACETONE	67-64-1	60-100
PROPANE	74-98-6	10-30
METHYL ETHYL KETONE	78-93-3	5-10
ETHYL 3-ETHOXYPROPIONATE	763-69-9	1-5

Section 04: First aid measures

Eye contact..... In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Obtain medical attention.

Ingestion..... Do not induce vomiting. If ingestion is suspected, contact physician or poison control center immediately. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person.

Inhalation..... If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention.

Skin contact..... Remove all contaminated clothing and immediately wash the exposed areas with copious amounts of water for a minimum of 30 minutes or up to 60 minutes for critical body areas. If irritation persists, seek medical attention.

Additional information..... Treat victims symptomatically. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet.

PRODUCT: NEX6010 CUSTOM FILLING SYSTEM**Section 05: Fire fighting measures**

Extinguishing media..... Carbon dioxide. Water fog. Dry chemical. Foam.
 Hazardous combustion products..... Hydrocarbon fumes and smoke. Carbon monoxide where combustion is incomplete.
 Special fire fighting procedures..... Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture. Keep run-off water from entering sewers and other waterways. Dike for water control.

Section 06: Accidental release measures

Leak/spill..... Ventilate. Eliminate all sources of ignition. Evacuate all non-essential personnel. Contain the spill. Avoid all personal contact. Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations. Prevent runoff into drains, sewers, and other waterways. Absorb with earth, sand, or another dry inert material. Do not use combustible materials such as sawdust as an absorbant. Shovel into suitable unsealed containers, transport to well-ventilated area (outside) and treat with neutralizing solution: mixture of water (80%) with non-ionic surfactant Tergitol TMN-10 (20%); or water (90%), concentrated ammonia (3-8%) and detergent (2%).

Section 07: Handling and storage

Handling procedures..... Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Avoid breathing vapours or mist. Ground handling equipment. Handle and open container with care. Employees should wash hands and face before eating or drinking. Keep away from heat, sparks, and open flame.
 Storage needs..... Keep away from heat, sparks, and open flames. Keep container closed when not in use. Store away from oxidizing and reducing materials. Store away from sunlight. Do not store above 49C.

Section 08: Exposure controls / personal protection

Protective equipment
 Eye/type..... Chemical safety goggles should be worn. Plastic face shields should be worn in addition to safety goggles for complete face protection.
 Respiratory/type..... Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits.
 Gloves/ type..... Not normally required. Gloves impervious to the material are recommended.
 Clothing/type..... Wear adequate protective clothes.
 Footwear/type..... Safety boots per local regulations.
 Other/type..... Emergency showers and eye wash stations should be available.
 Ventilation requirements..... Local exhaust at points of emission.
 Exposure limits

Ingredients	TWA	ACGIH TLV		PEL	OSHA PEL		REL	NIOSH
			STEL			STEL		
ACETONE	500 ppm		750 ppm	1,000 ppm		Not established		250 ppm
PROPANE	1,000 ppm		No data	1,000 ppm		No data		1,000 ppm
METHYL ETHYL KETONE	200 ppm		300 ppm	200 ppm		Not established		200 ppm / 300 ppm 15 minutes
ETHYL 3-ETHOXYPROPIONATE	not established		not established	not established		not established		not established

Section 09: Physical and chemical properties

Physical state..... Aerosol.
 Colour..... Clear, colourless.
 Odour..... Hydrocarbon odour.
 Odour threshold (ppm)..... No data.
 Vapour pressure (mm Hg)..... 75-80 psig @ 20c.
 Vapour density (air=1)..... >1.
 pH..... Not applicable.
 Specific gravity..... Liquid: 0.793 aerosol: 0.722.
 Freezing point (deg C)..... -95.
 Solubility..... Insoluble.
 Boiling point (deg C)..... 136°C (276°F).
 Evaporation rate..... Slower than n-butyl acetate.
 Flash point (deg C), method..... < -104. Aerosol flame projection < 100 cm.

PRODUCT: NEX6010 CUSTOM FILLING SYSTEM**Section 09: Physical and chemical properties**

Auto ignition temperature (deg C)..... 450.
 Upper flammable limit (% vol)..... 9.5.
 Lower flammable limit (% vol)..... 2.0.
 Coefficient of water/oil distribution..... No data.
 % Volatile by volume..... 100.
 VOC..... 2.09 g/l - 1.74 lb/usg.
 Viscosity..... No data.

Section 10: Stability and reactivity

Reactivity conditions..... Avoid heat, sparks and flames. Explosive reactions can occur in the presence of strong oxidizing agents. Risk of bursting of closed containers due to an increase in pressure.
 Stability..... Stable at normal temperatures and pressures.
 Incompatibility..... Keep away from heat. Strong oxidizing agents, mineral acids, and alkalines.
 Hazardous products of decomposition..... See hazardous combustion products.
 Hazardous polymerization..... Hazardous polymerization will not occur.

Section 11: Toxicological information

Route of entry Eye contact. Skin contact. Skin absorption. Inhalation.
 Effects of acute exposure..... Contact with eyes may cause irritation. Contact with skin may cause moderate to severe irritation. If ingested, this product may be absorbed and result in gastrointestinal irritation, nausea, vomiting, and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal. Inhalation of vapours causes irritation to the nose, throat and respiratory tract. Inhalation of higher concentration may result in central nervous system depression and unconsciousness.
 Effects of chronic exposure..... Prolonged or repeated skin contact may cause drying or cracking of skin. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal .
 Sensitizing capability of material..... May cause sensitization by skin contact.
 Toxicological Data

Ingredients	LC50-inh, rat	LD50-Oral,rat
ACETONE	50,100 mg/m ³ 8 hours rat inhalation	5,800 mg/kg rat oral
PROPANE	>1,464 mg/L 15 minutes rat	No data
METHYL ETHYL KETONE	>5,000 ppm 6 hours rat	3,400 mg/kg rat oral
ETHYL 3-ETHOXYPROPIONATE	>998 ppm 6 hours	4,309 mg/kg rat oral 4,080 mg/kg rabbit dermal

Section 12: Ecological information

Environmental..... Do not allow to enter waters, waste water or soil.
 Biodegradability..... No data.

Section 13: Disposal considerations

Waste disposal..... This material and its container must be disposed of as hazardous waste. Avoid release to the environment. Contents under pressure. Do not puncture, incinerate or expose to heat, even when empty.

Section 14: Transport information

TDG Classification (Road)..... UN1950 - AEROSOLS, flammable - Class 2.1 - This product meets limited quantity exemption when shipped in containers less than 1 Litre.

Section 15: Regulatory information

WHMIS classification..... A. B5. D1B. D2B.
 CEPA status..... On Domestic Substances List (DSL).
 Section 313..... Methyl ethyl ketone.
 OSHA..... This product is considered hazardous under the OSHA Hazard Communication Standard.
 SARA Title III
 Section 302 - extremely hazardous None.
 substances
 Section 311/312 - hazard categories..... Immediate health, delayed health, fire hazard.
 EPA hazardous air pollutants (HAPS) None.
 40CFR63
 TSCA inventory status..... All components are listed.
 California Proposition 65..... This product does not contain any chemical(s) known to the State of California to cause cancer or reproductive toxicity.

PRODUCT: NEX6010 CUSTOM FILLING SYSTEM

Section 16: Other information

Prepared by: REGULATORY AFFAIRS.

Telephone number:..... (800) 387-7981.

Disclaimer:..... DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.

Disclaimer:..... Regulatory Affairs