


PRODUCT: NEX7116 PREMIUM SELF LEVELING FINISHING GLAZE
Section 01: Chemical product and company identification

Product name..... NEX7116 PREMIUM SELF LEVELING FINISHING GLAZE
 Manufactured for..... AUTO REFINISH DISTRIBUTORS INC
 PO Box 38484
 Houston, TX 77238

24 hour emergency number..... IN CANADA CALL CANUTEC (613) 996-6666-IN THE UNITED STATES CALL
 CHEMTREC (800) 424-9300.

Material use..... Automotive.
 Chemical family..... Mixture.
 Preparation date..... May 22, 2014.
 Hazard rate
 NFPA rating..... Health: 2 Fire: 3 Reactivity: 0.
 HMIS..... H: 2* F: 3 R: 0.

Section 02: Hazards identification


Signal Word..... WARNING.
 Hazard Classification..... Flammable Liquid 3. Aspiration Toxicity 2. Carcinogen 2. Eye Irritant 2. Skin Irritant 2.
 STOT SE 3. STOT RE 2.

Hazard Description..... H226 Flammable liquid and vapour. H305 May be harmful if swallowed and enters airways.
 H315 Causes skin irritation. H320 Causes eye irritation. H336 May cause drowsiness or
 dizziness. H351 This product contains ingredients that are suspected of causing cancer.
 H373 May cause damage to the liver and kidneys through prolonged or repeated contact.

Precautionary Statements..... P202 Do not handle this product until all safety instructions have been read and
 understood. P210 Keep away from heat, sparks, open flames and hot surfaces. No
 smoking. P211 Do not spray on an open flame or other ignition sources. P233 Keep
 container tightly closed. P240 Ground and bond container and receiving equipment. P241
 Use explosion proof equipment. P242 Use only non-sparking tools. P243 Take
 precautionary measures against static discharge. P251 Do not pierce or burn container,
 even after use. P261 Avoid breathing mists, vapours and sprays. P264 Wash thoroughly
 after handling. P270 Do not eat drink or smoke while using this product. P271 Use only
 outdoors or in a well ventilated area. P273 Avoid release to the environment. P280 Wear
 protective gloves and eye protection. P284 In case of inadequate ventilation wear
 respiratory protection.

Section 03: COMPOSITION/INFORMATION ON INGREDIENTS

| Hazardous Ingredients | CAS # | Wt. % |
|-----------------------|------------|---------|
| STYRENE | 100-42-5 | 10-30 |
| TALC | 14807-96-6 | 10-30 |
| CALCIUM CARBONATE | 1317-65-3 | 7-13 |
| TITANIUM DIOXIDE | 13463-67-7 | 1-5 |
| QUARTZ | 14808-60-7 | 0.1-1.0 |
| CHLORITE | 1318-59-8 | 0.1-1.0 |
| C I PIGMENT YELLOW 53 | 8007-18-9 | 0.1-1.0 |
| N,N-DIMETHYLACETAMIDE | 127-19-5 | 0.1-1.0 |

Section 04: First aid measures

Eye contact..... In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at
 least 15 minutes. Obtain medical attention.

Skin contact..... Immediately remove all contaminated clothing; flush skin with water for at least 15 minutes.
 If irritation persists, seek medical attention.

Inhalation..... If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is
 difficult, give oxygen, obtain medical attention.

PRODUCT: NEX7116 PREMIUM SELF LEVELING FINISHING GLAZE**Section 04: First aid measures**

Ingestion..... Rinse mouth with water. Do not induce vomiting. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person. The main hazard from ingestion is aspiration of the liquid into the lungs.

Additional information..... Treat victims symptomatically. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet.

Section 05: Fire fighting measures

Extinguishing media..... "Alcohol" foam, CO₂, dry chemical.

Special fire fighting procedures..... Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Solvent vapours may be heavier than air and may build up and travel along the ground to an ignition source, which may result in a flash back to the source of the vapours. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture.

Hazardous combustion products..... May produce hazardous fumes. Oxides of carbon (CO, CO₂). Dense black smoke.

Section 06: Accidental release measures

Leak/spill..... Isolate area and keep unauthorized people away. Do not walk through spilled material. Wear recommended protective equipment. Ventilate. Open windows and doors to allow air circulation. Dike area to prevent spreading. The use of absorbent socks or spill pillows may be required. Stop leak if safe to do so. Prevent runoff into drains, sewers, and other waterways. Cover spill with absorbent material and place in appropriate containers. Spill area can be washed with water. Collect wash water for approved disposal. Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations.

Section 07: Handling and storage

Handling procedures..... Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Avoid breathing vapours or mist. Ground handling equipment. Handle and open container with care. Employees should wash hands and face before eating or drinking. Keep away from heat, sparks, and open flame.

Storage needs..... Store in a cool, dry and well ventilated area. Keep container closed when not in use. Store away from all sources of heat and ignition. Store away from oxidizing and reducing materials.

Section 08: Exposure controls / personal protection

Protective equipment

Eye/type..... Chemical safety goggles. Chemical safety goggles and full faceshield if a splash hazard exists.

Respiratory/type..... Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits. Be sure to use NIOSH approved respirator or equipment. Do not exceed the use limits of the respirator.

Gloves/ type..... Chemical resistant gloves.

Clothing/type..... Wear adequate protective clothes.

Footwear/type..... Safety boots per local regulations.

Other/type..... Eye wash facility and emergency shower should be in close proximity.

Ventilation requirements..... Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits. Local mechanical exhaust ventilation should be used at sources of air contamination, such as open process equipment, or during purging operations, to capture gases and fumes that may be emitted. Standard reference sources regarding industrial ventilation (ie. ACGIH industrial ventilation) should be consulted for guidance about adequate ventilation. .

Exposure limits

| Ingredients | TWA | ACGIH TLV | | OSHA PEL | NIOSH |
|-------------------|-------------------------|-----------|----------------------|-----------------|------------------------|
| | | STEL | REL | | |
| STYRENE | 20 ppm | 40 ppm | 100 ppm | Not established | 100 ppm |
| TALC | 2 mg/m ³ | No data | 2 mg/m ³ | No data | 2 mg/m ³ |
| CALCIUM CARBONATE | No data | No data | 5 mg/m ³ | No data | 5 mg/m ³ |
| TITANIUM DIOXIDE | 10 mg/m ³ | No data | 15 mg/m ³ | No data | No data |
| QUARTZ | 0.025 mg/m ³ | No data | No data | No data | 0.05 mg/m ³ |
| CHLORITE | No data | No data | No data | No data | No data |

PRODUCT: NEX7116 PREMIUM SELF LEVELING FINISHING GLAZE**Section 08: Exposure controls / personal protection**

| Ingredients | TWA | ACGIH TLV STEL | PEL | OSHA PEL STEL | REL | NIOSH |
|-----------------------|---------|-------------------|---------|------------------|---------|---------|
| C I PIGMENT YELLOW 53 | No data | No data | No data | No data | No data | No data |
| N,N-DIMETHYLACETAMIDE | No data | No data | No data | No data | No data | No data |

Section 09: Physical and chemical properties

| | |
|--|--------------------------------|
| Physical state..... | Liquid. |
| Colour..... | Light yellow. |
| Odour..... | Hydrocarbon odour. |
| Specific gravity..... | 0.97 - 8.2 lb/USG. |
| Odour threshold (ppm)..... | 0.14 (Styrene). |
| Vapour pressure (mm Hg)..... | No data. |
| Vapour density (air=1)..... | >1. |
| pH..... | No data. |
| Freezing point (deg C)..... | No data. |
| Solubility..... | No data. |
| Boiling point (deg C)..... | 145. |
| Evaporation rate..... | No data. |
| Flash point (deg C), method..... | 31. |
| Auto ignition temperature (deg C)..... | 490. |
| Upper flammable limit (% vol)..... | 6.8. |
| Lower flammable limit (% vol)..... | 0.9. |
| Coefficient of water/oil distribution..... | No data. |
| VOC..... | 55.12 g/l - 0.46 lb/usg. |
| Viscosity..... | 15,400 cps Spindle C @ 10 rpm. |

Section 10: Stability and reactivity

| | |
|--|--|
| Stability..... | Stable at normal temperatures and pressures. |
| Reactivity conditions..... | Avoid heat, sparks and flames. Explosive reactions can occur in the presence of strong oxidizing agents. |
| Incompatibility..... | Keep away from heat. Incompatible with strong oxidizers. |
| Hazardous products of decomposition..... | See hazardous combustion products. |
| Hazardous polymerization..... | Will not occur under normal temperature and pressure. |

Section 11: Toxicological information

| | |
|----------------------------------|--|
| Route of entry | Eye contact. Skin contact. Inhalation. Ingestion. |
| Effects of acute exposure..... | The aromatic hydrocarbon solvents in this product can be irritating to the eyes, nose and throat. In high concentration, they may cause central nervous system depression and narcosis characterized by nausea, lightheadedness and dizziness from overexposure by inhalation. |
| Effects of chronic exposure..... | Breathing high concentrations of vapour may cause anesthetic effects and serious health effects. Repeated contact with the skin may cause dermatitis in sensitive individuals. Prolonged or repeated exposure may lead to liver, kidney or central nervous system symptoms. Ingestion may cause adverse systemic effects. |
| Carcinogenicity of material..... | Styrene is classified by IARC as 'possibly carcinogenic to humans' based on 'inadequate evidence' in humans, 'limited evidence' in animals and other 'relevant data'. Studies in humans exposed to Styrene for long periods of time have not demonstrated any carcinogenic effects. Calcium carbonate may contain at least 0.1% of a carcinogen (crystalline silica). Quartz (Crystalline Silica) is a suspect carcinogen per IARC and NTP. IARC has classified Titanium Dioxide as a group 2B carcinogen. |

Toxicological Data

| Ingredients | LC50-inh, rat | LD50-Oral,rat |
|-----------------------|-------------------|--|
| STYRENE | 2770 ppm 4 hr rat | 5000 mg/kg rat oral |
| TALC | No data | No data |
| CALCIUM CARBONATE | No data | 6450 mg/kg rat oral |
| TITANIUM DIOXIDE | No data | No data |
| QUARTZ | No data | No data |
| CHLORITE | No data | No data |
| C I PIGMENT YELLOW 53 | No data | No data |
| N,N-DIMETHYLACETAMIDE | 2475 ppm rat | 4300 mg/kg oral rat; 2240 mg/kg dermal rat |

PRODUCT: NEX7116 PREMIUM SELF LEVELING FINISHING GLAZE**Section 12: Ecological information**

Environmental..... Do not allow to enter waters, waste water or soil.
 Biodegradability..... No data.

Section 13: Disposal considerations

Waste disposal..... Empty containers must be handled with care due to product residue. Dispose of as an industrial waste in a manner acceptable to good waste management practice and in accordance with applicable local, provincial/State or federal regulations.

Section 14: Transport information

TDG Classification (Road)..... UN3269 - Polyester Resin Kit - Class 3 - PG III - This product meets the criterial for Limited Quantity Exemptions when packaged in containers less than 5 litres .
 IATA Classification (Air)..... UN3269 - Polyester Resin Kit - Class 3 - PG III.
 IMDG Classification (Marine)..... UN3269 - Polyester Resin Kit - Class 3 - PG III - EmS: F-E S-D.
 Marine Pollutant..... No.

Section 15: Regulatory information

WHMIS classification..... B2, D2A, D2B.
 CEPA status..... On Domestic Substances List (DSL).
 OSHA..... This product is considered hazardous under the OSHA Hazard Communication Standard.
 SARA Title III
 Section 302 - extremely hazardous substances None.
 Section 311/312 - hazard categories..... Immediate health, delayed health, fire hazard.
 Section 313..... Styrene.
 EPA hazardous air pollutants (HAPS) Styrene.
 40CFR63
 TSCA inventory status..... All components are listed.
 California Proposition 65..... This product contains Crystalline Silica (Quartz) known to the State of California to cause cancer. California is in the process of listing Titanium Dioxide to Proposition 65 as a known carcinogen. California EPA's Office of Environmental Health Hazard Assessment (OEHHA) has withdrawn Styrene as a potential addition to the list of substances known to the state to cause cancer (March 1, 2013).

Section 16: Other information

Prepared by: REGULATORY AFFAIRS.
 Telephone number:..... (800) 387-7981.
 Disclaimer:..... DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.
 Disclaimer:..... Regulatory Affairs

**PRODUCT: BLUE CREAM HARDENER****Section 01: Chemical product and company identification**

Product name..... BLUE CREAM HARDENER
 Manufactured for..... AUTO REFINISH DISTRIBUTORS INC
 PO Box 38484
 Houston, TX 77238

24 hour emergency number..... In Canada call Canutec (613) 996-6666 - In the United States call Chemtrec (800) 424-9300.

Material use..... Accelerator and activator.
 Chemical family..... Mixture.
 Preparation date..... January 17, 2014.
 Hazard rate
 NFPA rating..... Health: 2 Fire: 2 Reactivity: 2.
 HMIS..... H: 2 F: 2 R: 2.

Section 02: Hazards identification

Signal Word..... DANGER.
 Hazard Classification..... Acute Toxicity 4. Eye Irritant 2. Skin Irritant 2. Skin Sensitizer 1. Aspiration Toxicity 1. Flammable Liquid 4.
 Hazard Description..... H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H320 Causes eye irritation. H332 Harmful if inhaled. H227 Combustible liquid.
 Precautionary Statements..... P243 Take precautionary measures against static discharge. P251 Do not pierce or burn container, even after use. P261 Avoid breathing dust. P261 Avoid breathing mists, vapours and sprays. P264 Wash thoroughly after handling. P270 Do not eat drink or smoke while using this product. P271 Use only outdoors or in a well ventilated area. P273 Avoid release to the environment. P280 Wear protective gloves and eye protection. P202 Do not handle this product until all safety instructions have been read and understood. P284 In case of inadequate ventilation wear respiratory protection. P410 Protect from sunlight. P412 Do not expose to temperature exceeding 50C / 122F. P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P211 Do not spray on an open flame or other ignition sources. P233 Keep container tightly closed. P235 Keep cool. P240 Ground and bond container and receiving equipment. P241 Use explosion proof equipment. P242 Use only non-sparking tools.
 Note This product is an oxidizer.

Section 03: COMPOSITION/INFORMATION ON INGREDIENTS

| Hazardous Ingredients | CAS # | Wt. % |
|---------------------------|-------------|-------|
| BENZYOL PEROXIDE | 96-36-0 | 40-70 |
| NON-PHTHALATE PLASTICIZER | PROPRIETARY | 15-40 |
| SILICA, AMORPHOUS | 7631-86-9 | 1-5 |
| CALCIUM CARBONATE | 1317-65-3 | 1-5 |

Section 04: First aid measures

Eye contact..... In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Obtain medical attention.
 Skin contact..... Remove all contaminated clothing and immediately wash the exposed areas with copious amounts of water for a minimum of 30 minutes or up to 60 minutes for critical body areas. If irritation persists, seek medical attention.
 Inhalation..... If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention.
 Ingestion..... Do not induce vomiting. If ingestion is suspected, contact physician or poison control center immediately. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person.

PRODUCT: BLUE CREAM HARDENER**Section 04: First aid measures**

Additional information..... Treat victims symptomatically. The main hazard from ingestion is aspiration of the liquid into the lungs. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet.

Section 05: Fire fighting measures

Extinguishing media..... "Alcohol" foam, CO₂, dry chemical.
 Hazardous combustion products..... Oxides of carbon (CO,CO₂). Benzoic acid. Hydrocarbons.
 Special fire fighting procedures..... Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Fight fire like a fuel oil fire.
 Unusual fire / explosion hazards..... Fire hazard increases when material becomes dry. Vapours may be heavier than air. May travel long distances along the ground before igniting and flashing back to vapour source.

Section 06: Accidental release measures

Leak/spill..... Ventilate. Eliminate all sources of ignition. Isolate area and keep unauthorized people away. Do not walk through spilled material. Contain the spill. Prevent runoff into drains, sewers, and other waterways. Absorb with earth, sand, or another dry inert material. Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations.

Section 07: Handling and storage

Handling procedures..... Keep away from heat, sparks, and open flame. Do not breathe vapours, mist or dust. Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Handle in accordance with good industrial hygiene and safety practices. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Ground handling equipment. Handle and open container with care. Employees should wash hands and face before eating or drinking.
 Storage needs..... Keep away from heat, sparks, and open flames. Keep container closed when not in use. Store in a cool dry place away from organic materials.

Section 08: Exposure controls / personal protection

Protective equipment
 Eye/type..... Liquid chemical goggles.
 Respiratory/type..... Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits.
 Gloves/ type..... Chemical resistant gloves.
 Clothing/type..... Wear adequate protective clothes.
 Footwear/type..... Safety boots per local regulations.
 Other/type..... Emergency showers and eye wash stations should be available.
 Ventilation requirements..... Local exhaust at points of emission.
 Exposure limits

| Ingredients | ACGIH TLV | | PEL | OSHA PEL | | REL | NIOSH |
|---------------------------|-----------|---------|---------------------|----------|---------|---------------------|---------------------|
| | TWA | STEL | | STEL | STEL | | |
| BENZYOL PEROXIDE | No data | No data | No data | No data | No data | No data | No data |
| NON-PHTHALATE PLASTICIZER | No data | No data | No data | No data | No data | No data | No data |
| SILICA, AMORPHOUS | No data | No data | No data | No data | No data | No data | No data |
| CALCIUM CARBONATE | No data | No data | 5 mg/m ³ | No data | No data | 5 mg/m ³ | 5 mg/m ³ |

Section 09: Physical and chemical properties

Physical state..... Paste.
 Colour..... Blue.
 Odour..... Mild odour. Ester odour.
 Odour threshold (ppm)..... No data.
 Vapour pressure (mm Hg)..... <1 mm Hg @ 20C.
 Vapour density (air=1)..... >1. Heavier than air.
 pH..... Neutral.
 Specific gravity..... 1.2.
 Freezing point (deg C)..... No data.
 Solubility..... Slightly soluble in water.
 Boiling point (deg C)..... Decomposes.
 Evaporation rate..... <1. Slower than ether.
 Flash point (deg C), method..... 84 Seta Flash Closed Cup.

PRODUCT: BLUE CREAM HARDENER**Section 09: Physical and chemical properties**

Auto ignition temperature (deg C)..... No data.
 Upper flammable limit (% vol)..... No data.
 Lower flammable limit (% vol)..... No data.
 Coefficient of water/oil distribution..... No data.
 % Volatile by weight..... 10-20.
 VOC..... 0.0 g/L - 0.0 lb/USG.
 Viscosity..... No data.

Section 10: Stability and reactivity

Stability..... Stable at normal temperatures and pressures.
 Reactivity conditions..... Avoid heat, sparks and flames. Possible decomposition if exposed to elevated temperatures.
 Incompatibility..... Avoid contact in uncontrolled conditions with: . Organic chemicals. Inorganic acids. Strong oxidizers. Accelerators. Reducing agents. Alcohols. Amines. Strong bases.
 Hazardous products of decomposition..... See hazardous combustion products.
 Hazardous polymerization..... Hazardous polymerization will not occur.

Section 11: Toxicological information

Route of entry Eye contact. Skin contact. Ingestion. Inhalation.
 Effects of acute exposure..... Contact with paste may result in irritation, redness, tearing, and blurred vision. May cause skin irritation. If ingested, this product may be absorbed and result in gastrointestinal irritation, nausea, vomiting, and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.
 Effects of chronic exposure..... Prolonged or repeated skin contact may cause drying or cracking of skin.
 Sensitizing capability of material..... Prolonged or repeated exposure may result in skin sensitization.
 Carcinogenicity of material..... This product is not listed by NTP, IARC or regulated as a carcinogen by OSHA.
 Toxicological Data

| Ingredients | LC50-inh, rat | LD50-Oral, rat |
|---------------------------|---------------|---------------------|
| BENZYOL PEROXIDE | No data | 7710 mg/kg Rat Oral |
| NON-PHTHALATE PLASTICIZER | No data | No data |
| SILICA, AMORPHOUS | No data | 3160 mg/kg rat oral |
| CALCIUM CARBONATE | No data | 6450 mg/kg rat oral |

Section 12: Ecological information

Environmental..... Do not allow to enter waters, waste water or soil.
 Biodegradability..... No data.

Section 13: Disposal considerations

Waste disposal..... Empty containers must be handled with care due to product residue. Dispose of as an industrial waste in a manner acceptable to good waste management practice and in accordance with applicable local, provincial/State or federal regulations.

Section 14: Transport information

TDG Classification (Road)..... The product meets the Limited Quantity exemption when packaged in containers less than 0.5 kg. For packages greater than 0.5 kg, the classification is - Organic Peroxide, Type E, Solid (Benzoyl Peroxide) - Class 5.2 - UN3108 - PG II.
 IATA Classification (Air)..... Organic peroxide, Type E, Solid (Benzoyl peroxide) - UN3108 - Class 5.2 - PG II.
 IMDG Classification (Marine)..... Organic Peroxide, Type E, Solid (Benzoyl peroxide) - UN3108 - Class 5.2 - PG II.
 Marine Pollutant..... No.

Section 15: Regulatory information

WHMIS classification..... B3. C. D2B. F.
 CEPA status..... On Domestic Substances List (DSL).
 Section 313..... Benzoyl peroxide.
 OSHA..... This product is considered hazardous under the OSHA Hazard Communication Standard.
 SARA Title III
 Section 302 - extremely hazardous None.
 substances
 Section 311/312 - hazard categories..... Immediate health, delayed health.
 EPA hazardous air pollutants (HAPS) None.
 40CFR63
 TSCA inventory status..... All components are listed.

PRODUCT: BLUE CREAM HARDENER

Section 15: Regulatory information

California Proposition 65..... This product does not contain any chemical(s) known to the State of California to cause cancer or reproductive toxicity.

Section 16: Other information

Prepared by: Regulatory Affairs.

Telephone number:..... (800) 387-7981.

Disclaimer:.....
DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.