

**PRODUCT: NEX9101 TRUCK BED LINER COATING TINTABLE PART A****Section 01: Chemical product and company identification**

Product name..... NEX9101 BUCK SHOT TRUCK BED LINER COATING TINTABLE PART A
 Manufactured for..... AUTO REFINISH DISTRIBUTORS INC
 PO Box 38484
 Houston, TX 77238

24 hour emergency number:..... IN CANADA CALL CANUTEC (613) 996-6666-IN THE UNITED STATES CALL
 CHEMTREC (800) 424-9300.

Material use..... Paints.
 Chemical family..... Acrylic coating.
 Preparation date..... September 29, 2013.
 Hazard rate
 NFPA rating..... Health: 2 Fire: 3 Reactivity: 0.
 HMIS..... H: 2 F: 3 R: 0.

Section 02: Hazards identification

Signal Word..... DANGER.
 Hazard Classification..... Flammable Liquid 2. Eye Irritant 2. Skin Irritant 2. Acute Toxicity 4. Aspiration Toxicity 1.
 Carcinogen 2. Reproductive 2.
 Hazard Description..... H225 Highly flammable liquid and vapour. H305 May be harmful if swallowed and enters
 airways. H313 May be harmful in contact with skin. H315 Causes skin irritation. H320
 Causes eye irritation. H332 Harmful if inhaled. H351 This product contains ingredients that
 are suspected of causing cancer. H361 This product contains ingredients that are
 suspected of damaging fertility or the unborn child.
 Precautionary Statements..... P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P211 Do
 not spray on an open flame or other ignition sources. P233 Keep container tightly closed.
 P235 Keep cool. P240 Ground and bond container and receiving equipment. P241 Use
 explosion proof equipment. P242 Use only non-sparking tools. P243 Take precautionary
 measures against static discharge. P261 Avoid breathing mists, vapours and sprays. P264
 Wash thoroughly after handling. P270 Do not eat drink or smoke while using this product.
 P271 Use only outdoors or in a well ventilated area. P280 Wear protective gloves and eye
 protection. P284 In case of inadequate ventilation wear respiratory protection.

Section 03: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredients	CAS #	Wt. %
SOLVENT NAPHTHA, LIGHT AROMATICS	64742-95-6	3-7
XYLENE	1330-20-7	1-5
1,2,4-TRIMETHYLBENZENE	95-63-6	1-5
1,3,5-TRIMETHYLBENZENE	108-67-8	1-5
N-BUTYL ACETATE	123-86-4	1-5
ETHYLBENZENE	100-41-4	0.1-1.0
2,4-PENTADIONE	123-54-6	0.1-1.0
2 BUTOXY ETHANOL	111-76-2	0.1-1.0
PHOSPHORIC ACID	7664-38-2	0.1-1.0
METHYL ISOBUTYL KETONE	108-10-1	0.1-1.0
PROPYL BENZENE	103-65-1	0.1-1.0

PRODUCT: NEX9101 TRUCK BED LINER COATING TINTABLE PART A**Section 04: First aid measures**

Eye contact.....	In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Obtain medical attention.
Skin contact.....	Remove all contaminated clothing and immediately wash the exposed areas with copious amounts of water for a minimum of 30 minutes or up to 60 minutes for critical body areas. If irritation persists, seek medical attention.
Inhalation.....	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention.
Ingestion.....	If ingestion is suspected, contact physician or poison control center immediately. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person.
Additional information.....	Treat victims symptomatically. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet.

Section 05: Fire fighting measures

Extinguishing media.....	"Alcohol" foam, CO2, dry chemical.
Hazardous combustion products.....	Oxides of carbon (CO, CO2). By fire: protect against potentially toxic and irritating fumes.
Special fire fighting procedures.....	Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Solvent vapours may be heavier than air and may build up and travel along the ground to an ignition source, which may result in a flash back to the source of the vapours. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture.

Section 06: Accidental release measures

Leak/spill.....	Ventilate. Eliminate all sources of ignition. Contain the spill. Avoid all personal contact. Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations. Evacuate all non-essential personnel. Prevent runoff into drains, sewers, and other waterways. Absorb with earth, sand, or another dry inert material. Shovel into suitable unsealed containers, transport to well-ventilated area (outside) and treat with neutralizing solution: mixture of water (80%) with non-ionic surfactant Tergitol TMN-10 (20%); or water (90%), concentrated ammonia (3-8%) and detergent (2%).
-----------------	---

Section 07: Handling and storage

Handling procedures.....	Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Avoid breathing vapours or mist. Ground handling equipment. Handle and open container with care. Employees should wash hands and face before eating or drinking. Keep away from heat, sparks, and open flame.
Storage needs.....	Keep away from heat, sparks, and open flames. Keep container closed when not in use. Store away from oxidizing and reducing materials. Store away from sunlight.

Section 08: Exposure controls / personal protection

Protective equipment	
Eye/type.....	Liquid chemical goggles.
Respiratory/type.....	Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits.
Gloves/ type.....	Chemical resistant gloves.
Clothing/type.....	Wear adequate protective clothes.
Footwear/type.....	Safety boots per local regulations.
Other/type.....	Emergency showers and eye wash stations should be available.
Ventilation requirements.....	Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits. Local mechanical exhaust ventilation should be used at sources of air contamination, such as open process equipment, or during purging operations, to capture gases and fumes that may be emitted. Standard reference sources regarding industrial ventilation (ie. ACGIH industrial ventilation) should be consulted for guidance about adequate ventilation. In the event of thermal decomposition from overheating the product (decomposition begins at 380 C), evacuate the work area, shut down equipment, and provide general ventilation to the room prior to reoccupying.

Exposure limits

Ingredients	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL	NIOSH
SOLVENT NAPHTHA, LIGHT AROMATICS	not established	not established	not established	not established	not established	not established
XYLENE	100 ppm	150 ppm	100 ppm	Not established	Not established	Not established

PRODUCT: NEX9101 TRUCK BED LINER COATING TINTABLE PART A**Section 08: Exposure controls / personal protection**

Ingredients	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL	NIOSH
1,2,4-TRIMETHYLBENZE NE	25 ppm	Not established	Not established	Not established	25 ppm	
1,3,5-TRIMETHYLBENZE NE	Not established	Not established	Not established	Not established	25 ppm	
N-BUTYL ACETATE	150 ppm	200 ppm	150 ppm	200 ppm	150 ppm / STEL 200 ppm	
ETHYLBENZENE	100 ppm	125 ppm	100 ppm	No data	100 ppm / STEL 125 ppm	
2,4-PENTADIONE	No data	No data	No data	No data	No data	
2 BUTOXY ETHANOL	20 ppm	No data	50 ppm	25 ppm (vacated)	5 ppm	
PHOSPHORIC ACID	1 mg/m3	3 mg/m3	1 mg/m3	3 mg/m3	1 mg/m3	
METHYL ISOBUTYL KETONE	50 ppm	75 ppm	100 ppm	Not established	50 ppm / STEL 75 ppm	
PROPYL BENZENE	Not established	Not established	Not established	Not established	Not established	

Section 09: Physical and chemical properties

Physical state.....	Liquid.
Colour.....	Various colours.
Odour.....	Solvent odour.
Odour threshold (ppm).....	No data.
Vapour pressure (mm Hg).....	No data.
Vapour density (air=1).....	No data.
pH.....	Not applicable.
Specific gravity.....	1.095 - 9.128 lb/usg.
Freezing point (deg C).....	No data.
Solubility.....	Slightly soluble in water.
Boiling point (deg C).....	127.
Evaporation rate.....	No data.
Flash point (deg C), method.....	27. Tag Closed Cup.
Auto ignition temperature (deg C).....	370.
Upper flammable limit (% vol).....	6.6.
Lower flammable limit (% vol).....	0.9.
Coefficient of water/oil distribution.....	No data.
VOC.....	110.2 g/L - 0.92 lb/usg.
Viscosity.....	9200 cps unmixed/4000 cps mixed - Brookfield Spindle #5.

Section 10: Stability and reactivity

Stability.....	Stable at normal temperatures and pressures.
Reactivity conditions.....	Avoid heat, sparks and flames. Explosive reactions can occur in the presence of strong oxidizing agents.
Incompatibility.....	Keep away from heat. Incompatible with strong oxidizers.
Hazardous products of decomposition.....	See hazardous combustion products.
Hazardous polymerization.....	Will not occur under normal temperature and pressure.

Section 11: Toxicological information

Route of entry	Eye contact. Skin contact. Inhalation.
Effects of acute exposure.....	The aromatic hydrocarbon solvents in this product can be irritating to the eyes, nose and throat. In high concentration, they may cause central nervous system depression and narcosis characterized by nausea, lightheadedness and dizziness from overexposure by inhalation. Irritating to eyes, skin and respiratory system.
Effects of chronic exposure.....	Breathing high concentrations of vapour may cause anesthetic effects and serious health effects. Overexposure to vapour may cause central nervous system depression. May cause nausea, headache, dizziness, and drowsiness. Prolonged or repeated contact may cause eye and skin irritation. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal .
Carcinogenicity of material.....	Ethylbenzene is classified as an A3 known animal carcinogen. Methyl Isobutyl Ketone is possibly carcinogenic to humans (Group 2B).
Reproductive effects.....	High level exposure to Xylene in some animal studies have been reported to cause health effects on the developing embryo/fetus. The relevance of this to humans is not known. Chronic exposure to Ethylbenzene has been associated with reproductive effects among women.

Toxicological Data

PRODUCT: NEX9101 TRUCK BED LINER COATING TINTABLE PART A**Section 11: Toxicological information**

Ingredients	LC50-inh, rat	LD50-Oral, rat
SOLVENT NAPHTHA, LIGHT AROMATICS	5.2 mg/L 4 hours rat	>5,000 mg/kg rat oral >3,160 mg/kg rabbit dermal
XYLENE	6350 ppm 4 hours rat	>3523 mg/kg rat oral
1,2,4-TRIMETHYLBENZENE	>2,000 ppm 48 hours rat	3,280 mg/kg rat oral
1,3,5-TRIMETHYLBENZENE	No data	No data
N-BUTYL ACETATE	1.36 - 2.38 mg/L 4 hours rat	>3200 mg/kg rat oral >5000 mg/kg rabbit dermal
ETHYLBENZENE	No data	3,500 mg/kg rat oral 17,800 mg/kg rabbit dermal
2,4-PENTADIONE	1224 ppm/4 hour rat	55 mg/kg rat oral 790 mg/kg rabbit dermal
2 BUTOXY ETHANOL	450 ppm 4 hours rat	470 mg/kg oral rat 400 mg/kg dermal rabbit
PHOSPHORIC ACID	1.689 mg/L 1 hour rabbit	1,530 mg/kg rat oral 2,740 mg/kg rabbit dermal
METHYL ISOBUTYL KETONE	8.2 - 16.4 mg/L 4 hours rat	2080 mg/kg rat oral >16,000 mg/kg rabbit dermal
PROPYL BENZENE	No data	6,040 mg/kg rat oral

Section 12: Ecological information

Environmental..... Do not allow to enter waters, waste water or soil.
 Biodegradability..... No data.

Section 13: Disposal considerations

Waste disposal..... Empty containers must be handled with care due to product residue. This material and its container must be disposed of as hazardous waste. Avoid release to the environment.

Section 14: Transport information

TDG Classification (Road)..... UN1263 - PAINT - Class 3 - Packing Group II - This product meets limited quantity exemption when shipped in containers less than 5 litres.
 IATA Classification (Air)..... UN1263 - PAINT - Class 3 - Packing Group II.
 IMDG Classification (Marine)..... UN1263 - Paint - Class 3 - Packing Group II - EmS: F-E S-E.
 Marine Pollutant..... No.

Section 15: Regulatory information

WHMIS classification..... B2, D2A, D2B.
 CEPA status..... On Domestic Substances List (DSL).
 OSHA..... This product is considered hazardous under the OSHA Hazard Communication Standard.
 SARA Title III
 Section 302 - extremely hazardous substances None.
 Section 311/312 - hazard categories..... Immediate health, delayed health, fire hazard.
 Section 313..... Methyl Isobutyl Ketone. Xylene. Ethylbenzene.
 EPA hazardous air pollutants (HAPS) Methyl Isobutyl Ketone. Xylene. Ethylbenzene.
 40CFR63
 TSCA inventory status..... All components are listed.
 California Proposition 65..... This product contains Methyl Isobutyl Ketone (MIBK) known to the State of California to cause cancer. This product contains Ethylbenzene that is known to the State of California to cause cancer. California is in the process of listing Xylene on Proposition 65 as a reproductive toxin.

Section 16: Other information

Prepared by: REGULATORY AFFAIRS.
 Telephone number:..... (800) 387-7981.
 Disclaimer:..... DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.
 Disclaimer:..... Regulatory Affairs

**PRODUCT: NEX9101 TRUCK BED LINER COATING TINTABLE PART B****Section 01: Chemical product and company identification**

Product name..... NEX9101 TRUCK BED LINER COATING TINTABLE PART B
 Manufactured for..... AUTO REFINISH DISTRIBUTORS INC
 PO Box 38484
 Houston, TX 77238

24 hour emergency number..... IN CANADA CALL CANUTEC (613) 996-6666-IN THE UNITED STATES CALL
 CHEMTREC (800) 424-9300.

Material use..... Coatings.
 Chemical family..... Mixture.
 Preparation date..... January 16, 2013.
 Hazard rate
 NFPA rating..... Health: 2 Fire: 3 Reactivity: 0.
 HMIS..... H: 2 F: 3 R: 0.

Section 02: Hazards identification

Signal Word..... DANGER.
 Hazard Classification..... Flammable Liquid 2. STOT SE 3. Skin Sensitizer 1.
 Hazard Description..... H225 Highly flammable liquid and vapour. H317 May cause an allergic skin reaction. H336
 May cause drowsiness or dizziness.
 Precautionary Statements..... P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P233
 Keep container tightly closed. P235 Keep cool. P240 Ground and bond container and
 receiving equipment. P241 Use explosion proof equipment. P242 Use only non-sparking
 tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing
 mists, vapours and sprays. P264 Wash thoroughly after handling. P272 Contaminated
 work clothing should not be allowed out of the workplace. P280 Wear protective gloves and
 eye protection.

Section 03: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredients	CAS #	Wt. %
N-BUTYL ACETATE	123-86-4	30-60
HOMOPOLYMER OF HDI	28182-81-2	15-40
ACETIC ACID, TERT-BUTYL ESTER	540-88-5	10-30

Section 04: First aid measures

Eye contact..... In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at
 least 15 minutes. Check for and remove any contact lenses.
 Skin contact..... Immediately flush skin with plenty of soap and water. Remove contaminated clothing.
 Wash clothing before reuse.
 Inhalation..... If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is
 difficult, give oxygen, obtain medical attention.
 Ingestion..... Immediately call a physician. Drink plenty of water. Never give anything by mouth to an
 unconscious person. This product could cause chemical pneumonitis through aspiration of
 the product into the lungs following accidental ingestion. If spontaneous vomiting occurs
 have victim lean forward with head down to prevent aspiration of fluid into the lungs.
 Additional information..... In all cases, if irritation persists seek medical attention. In the event of an incident involving
 this product ensure that medical authorities are provided a copy of this safety data sheet.

Section 05: Fire fighting measures

Extinguishing media..... Carbon dioxide, dry chemical, foam. In cases of larger fires, water spray should be used.
 Special fire fighting procedures..... Firefighter should be equipped with self-contained breathing apparatus and full protective
 clothing to protect against potentially toxic and irritating fumes. Move containers from fire
 area if this can be done without risk. Keep run-off water from entering sewers and other
 waterways. Dike for water control.

PRODUCT: NEX9101 TRUCK BED LINER COATING TINTABLE PART B**Section 05: Fire fighting measures**

Hazardous combustion products..... Toxic vapours may be evolved upon exposure to heat or open flame.

Section 06: Accidental release measures

Leak/spill..... Evacuate all non-essential personnel. Avoid breathing vapours and skin contact. Remove sources of ignition if combustible or flammable vapours may be present and ventilate area. Dike area to prevent spreading. Prevent runoff into drains, sewers, and other waterways. Absorb residual material with sand, or other absorbent material. Shovel into suitable unsealed containers, transport to well-ventilated area (outside) and treat with neutralizing solution: mixture of water (80%) with non-ionic surfactant Tergitol TMN-10 (20%); or water (90%), concentrated ammonia (3-8%) and detergent (2%). Allow to stand for 72 hours. Decontaminate floor with decontaminate solution letting stand for at least 15 minutes.

Section 07: Handling and storage

Handling procedures..... This product must be manipulated by qualified personnel. Avoid eating and drinking in use. Avoid prolonged or repeated skin contact. Employees should wash hands and face before eating or drinking. Avoid breathing vapours or mist. Avoid skin and eye contact. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Handle and open container with care. Use adequate ventilation. Keep away from heat, sparks, and open flame.

Storage needs..... Store in tightly closed containers to prevent moisture contamination.

Section 08: Exposure controls / personal protection

Protective equipment

Eye/type..... Splash proof chemical goggles or 8" face shield. Contact lenses should not be worn when working with this chemical.

Respiratory/type..... Avoid breathing vapours. For operations where inhalation exposure can occur, a NIOSH-approved respirator may be necessary. Use air-purifying particulate / organic vapour cartridge respirator.

Gloves/ type..... Chemical resistant gloves. Practice good hygiene, wash thoroughly before handling any food.

Clothing/type..... Wear adequate protective clothes.

Footwear/type..... Safety boots per local regulations.

Other/type..... Eyewash fountain. Emergency shower should be in close proximity. Employees should wash their hands and face before eating, drinking, or using tobacco products.

Ventilation requirements..... Local exhaust at points of emission. Ventilation system must be designed vapor and explosion proof for handling solvent vapors.

Exposure limits

Ingredients	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL NIOSH
N-BUTYL ACETATE	150 ppm	200 ppm	150 ppm	200 ppm	150 ppm / STEL 200 ppm
HOMOPOLYMER OF HDI	5 mg/m3	Not established	5 mg/m3	Not established	5 mg/m3
ACETIC ACID, TERT-BUTYL ESTER	200 ppm	not established	200 ppm	not established	200 ppm

Section 09: Physical and chemical properties

Physical state..... Liquid.

Colour..... Light yellow.

Odour..... Solvent odour.

Odour threshold (ppm)..... No data.

Vapour pressure (mm Hg)..... No data.

Vapour density (air=1)..... >1.

pH..... Not applicable.

Specific gravity..... 0.97 - 8.09 lb/USG.

Freezing point (deg C)..... No data.

Solubility..... Insoluble.

Boiling point (deg C)..... > 98.

Evaporation rate..... No data.

Flash point (deg C), method..... 4.4 Closed Cup.

Auto ignition temperature (deg C)..... > 390.

Upper flammable limit (% vol)..... 7.5.

Lower flammable limit (% vol)..... 1.2.

Coefficient of water/oil distribution..... No data.

% Volatile by volume..... No data.

VOC..... 467.3 g/L - 3.9 lb/USG.

PRODUCT: NEX9101 TRUCK BED LINER COATING TINTABLE PART B**Section 09: Physical and chemical properties**

Viscosity..... 16.5 sec Zahn # 2 .

Section 10: Stability and reactivity

Stability..... Stable at normal temperatures and pressures.
 Reactivity conditions..... Exposure to high heat. Contact with moisture and other materials will react with isocyanates.
 Incompatibility..... Water, amines, strong bases, alcohols. Copper alloys.
 Hazardous polymerization..... Contact with moisture or other materials that react with isocyanates may cause polymerization. Temperatures above 177 C.
 Hazardous products of decomposition..... By fire and heat: carbon dioxide, carbon monoxide, oxides of nitrogen, hydrogen cyanide, isocyanates, isocyanic acid, other undetermined compounds.

Section 11: Toxicological information

Route of entry Eye contact. Skin contact. Inhalation.
 Effects of chronic exposure..... As a result of previous repeated overexposure or a single large dose, certain individuals develop sensitization which will cause them to react to a later exposure to product at levels well below the exposure limit. Prolonged or repeated skin contact may result in dry, defatted and cracked skin, causing increased susceptibility to infection.
 Skin contact..... Irritant. Can cause reddening, itching, and swelling. Persons previously sensitized can experience allergic reaction with symptoms of reddening, itching, swelling and rash. Prolonged contact may cause defatting of tissue.
 Eye contact..... Product liquid, aerosols or vapours are irritating. Damage is usually reversible. Can cause corneal damage. Can cause tearing, reddening and swelling.
 Inhalation (acute)..... Isocyanate vapour/mists at concentrations above the exposure limits can irritate (burning sensation) the mucous membranes in the respiratory tract. This can cause a runny nose, sore throat, coughing, chest discomfort, difficult breathing and reduced pulmonary functioning. Persons with preexisting, nonspecific bronchial hyperreactivity can respond to concentrations below the exposure limit with similar symptoms as well as asthma attack. Exposure well above the exposure limit may lead to bronchitis, bronchial spasm and pulmonary edema. Chemical or hypersensitive pneumonitis, with flu-like symptoms has also been reported. These symptoms can be delayed up to several hours after exposure. Excessive inhalation of vapours can cause respiratory irritation, dizziness, headache, vomiting and unconsciousness.
 Ingestion..... May be harmful if swallowed. May cause nausea, vomiting, and diarrhea. May cause central nervous system depression.
 Sensitizing capability of material..... In susceptible individuals.
 Carcinogenicity of material..... None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen.
 Reproductive effects..... No data.

Toxicological Data

Ingredients	LC50-inh, rat	LD50-Oral,rat
N-BUTYL ACETATE	1.36 - 2.38 mg/L 4 hours rat	>3200 mg/kg rat oral >5000 mg/kg rabbit dermal
HOMOPOLYMER OF HDI	390-453 mg/m3 rat 4 hours	> 5,000 mg/kg rat oral; > 5,000 mg/kg rabbit dermal
ACETIC ACID, TERT-BUTYL ESTER	>2,230 mg/m3 4 hours rat	4,100 mg/kg rat oral >2,000 mg/kg rabbit dermal

Section 12: Ecological information

Environmental..... Do not allow to enter waters, waste water or soil.
 Fish toxicity..... No data.

Section 13: Disposal considerations

Waste disposal..... Incineraton is the preferred method. Dispose of as an industrial waste in a manner acceptable to good waste management practice and in accordance with applicable local, provincial/State or federal regulations. Empty drums should be reconditioned by a properly licensed drum recycler.

Section 14: Transport information

TDG Classification (Road)..... UN1263 - Paint Related Material - Class 3 - Packing Group II - This product meets the Limited Quantity exemption when packaged in containers less than 5 liters.
 IATA Classification (Air)..... UN1263 - Paint Related Material - Class 3 - Packing Group II.
 IMDG Classification (Marine)..... UN1263 - Paint Related Material - Class 3 - Packing Group II - EmS: F-E S-E.
 Marine Pollutant..... No.

PRODUCT: NEX9101 TRUCK BED LINER COATING TINTABLE PART B**Section 15: Regulatory information**

WHMIS classification.....	B2. D2A. D2B.
OSHA.....	This product is considered hazardous under the OSHA Hazard Communication Standard.
CEPA status.....	On Domestic Substances List (DSL).
SARA Title III	
Section 302 - extremely hazardous substances	None.
Section 311/312 - hazard categories.....	Immediate health, delayed health, fire hazard.
Section 313.....	Hexamethylene diisocyanate.
EPA hazardous air pollutants (HAPS) 40CFR63	Hexamethylene diisocyanate.
TSCA inventory status.....	All components are listed.
California Proposition 65.....	This product does not contain any chemical(s) known to the State of California to cause cancer or reproductive toxicity.

Section 16: Other information

Prepared by:	REGULATORY AFFAIRS.
Telephone number:.....	(800) 387-7981.
Disclaimer:.....	DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.
Disclaimer:.....	Regulatory Affairs